



NOTES:  
 MECHANICAL  
 HOUSING & INSERT : PBT UL94V-0  
 CONTACT : PHOSPHOR BRONZE  
 CONTACT PLATING : CONTACT AREA SELECTIVE GOLD PLATING  
 SOLDER AREA TIN OVER NICKEL  
 SHIELD : BRASS PLATED NICKEL  
 MATING/UNMATING FORCE : 30N Max.  
 RETENTION STRENGTH : 50N FOR 60s±5  
 DURABILITY : 750 CYCLES MIN.

ELECTRICAL  
 VOLTAGE RATING : 125 VAC RMS  
 CURRENT RATING : 1.5 AMPS@25°C  
 CONTACT RESISTANCE : 20 mΩ MAX.  
 INSULATION RESISTANCE : 1000 MΩ MIN @500VDC  
 WITHSTAND VOLTAGE : 1000 VAC RMS CONTACT TO CONTACT, OR 1500 VDC CONTACT TO SCREEN AND TEST PANEL @0.5mA 50Hz OR 60Hz ONE MINUTE

ENVIRONMENTAL  
 STORAGE TEMPERATURE : -40°C TO +85°C  
 OPERATION TEMPERATURE : -40°C TO +85°C

 <b>E.S. GLOBAL TOP</b>		UNIT	mm
		REVISION	5
PRODUCT		RJ45 1X1 ANGLED ENTRY JACK	
DWG NO.		PART NO.	
EZC0745S-18S11-01			
PROJECTION	SCALE	SHEET	1 OF 1
			
		ANGLES ± 1°	