



RECOMMENDED PCB LAYOUT

NOTES:

MECHANICAL

- HOUSING & INSERT : PBT UL94V-0
- CONTACT : PHOSPHOR BRONZE Ø0.46mm
- CONTACT PLATING : GOLD PLATING AT CONTACT AREA, NICKEL 30U MIN. OVER ALL
- MATING/UNMATING FORCE : 30N/3.06kg Max.
- RETENTION STRENGTH : 50N Min. FOR 60s±5s
- DURABILITY : 750 CYCLES MIN.

ELECTRICAL

- VOLTAGE RATING : 125V AC RMS.
- CURRENT RATING : 1.5 AMP
- CONTACT RESISTANCE : 20mΩ Max.
- INSULATION RESISTANCE : 1000MΩ Min. @500 V DC
- WITHSTAND VOLTAGE : 1000V AC OR 1500V DC RMS @ 0.5mA 50Hz OR 60Hz ONE MINUTE

ENVIRONMENTAL

- STORAGE TEMPERATURE : -40°C~+85°C
- OPERATION TEMPERATURE : -40°C~+85°C

		UNIT	mm
		REVISION	06
PRODUCT		RJ11 1X2 SIDE ENTRY JACK	
DWG NO.		PART NO.	
EZC1011-26N11-01			
PROJECTION	SCALE	SHEET	1 OF 1

TOLERANCES
 00~15 ± 0.15
 15~30 ± 0.20
 30~ ± 0.25
 ANGLES ± 1°