

RECOMMENDED PCB LAYOUT

NOTES:
MECHANICAL
HOUSING


CONTACT
SHIELD
PLATING

DURABILITY
MATING/UNMATING FORCE
RETENTION STRENGTH

ELECTRICAL
VOLTAGE RATING
CURRENT RATING
CONTACT RESISTANCE
INSULATION RESISTANCE
DIELECTRIC STRENGTH

ENVIRONMENTAL
STORAGE
OPERATION

: THERMOPLASTIC GLASS FIBER
FILLED UL94V-0 BLACK
: PHOSPHOR BRONZE
: BRASS
: 15u" GOLD PLATING AT CONTACT
AREA NICKEL PLATING OVERALL
: 750 CYCLES MIN.
: 30N/3.06KG F MAX.
: 50N MIN.FOR 60S±5S
: 125 VAC RMS
: 1.5 AMP
: 20 mΩ MAX.
: 1000 MΩ MIN. @500V DC
: 1000V DC OR AC PEAK CONTACT
TO CONTACT OR 1500V DC OR AC
CONTACT TO SCREEN AND TEST
PANEL @0.5mA 50Hz OR 60Hz
ONE MINUTE



		UNIT	mm
		REVISION	03
PRODUCT		RJ45 1X2 SIDE ENTRY JACK WITH LED	
DWG NO.		PART NO.	
EZC1145-28S21-02			
PROJECTION	SCALE	SHEET	1 OF 1
		TOLERANCES	
		00~15 ± 0.15	
		15~30 ± 0.20	
		30~ ± 0.25	
		ANGLES ± 1°	