


NOTES:
MECHANICAL
HOUSING & INSERT : PA66 BLACK UL94V-0
CONTACT : PHOSPHOR BRONZE
CONTACT PLATING : CONTACT AREA SELECTIVE GOLD
 : SOLDER AREA TIN PLATING
 : OVER NICKEL
SHIELD : BRASS PLATED NICKEL
MATING/UNMATING FORCE : 30N Max.
RETENTION STRENGTH : 50N FOR 60s±5s.
DURABILITY : 750 CYCLES MIN.

ELECTRICAL
VOLTAGE RATING : 150V AC RMS.
CURRENT RATING : 1.5 AMPS @25°C
CONTACT RESISTANCE : 20mΩ Max.
INSULATION RESISTANCE : 1000MΩ Min. @500V DC
WITHSTAND VOLTAGE : 1000 V DC OR AC PEAK ONE
 : CONTACT TO ALL OTHER
 : CONTACTS CONNECTED
 : TOGETHER, 1500V DC OR AC
 : PEAK ALL CONTACTS CONNECTED
 : TOGETHER TO SHIELD. @0.5mA
 : 50Hz OR 60Hz ONE MINUTE

ENVIRONMENTAL
STORAGE TEMPERATURE : -40°C~+85°C
OPERATION TEMPERATURE : -40°C~+85°C



SGT <i>E.S. GLOBAL TOP</i>		UNIT	mm
		REVISION	08
PRODUCT		RJ45 1X4 SIDE ENTRY JACK WITH LED	
DWG NO. EZC1145-48S21-01		PART NO.	
PROJECTION	SCALE	SHEET	1 OF 1
		TOLERANCES	
		00~15 ± 0.15	
		15~30 ± 0.20	
		30~ ± 0.25	
		ANGLES ± 1°	