


RECOMMENDED PCB LAYOUT

LED GREEN



NOTES:

MECHANICAL  
HOUSING

: THERMOPLASTIC GLASS FIBER  
FILLED UL94V-0 BLACK

CONTACT  
PLATING

: PHOSPHOR BRONZE  
: GOLD PLATING AT CONTACT  
AREA NICKEL PLATING OVERALL

DURABILITY

: 750 CYCLES MIN.

MATING/UNMATING FORCE

: 30N/3.06KG F MAX.

RETENTION STRENGTH

: 50N MIN.FOR 60S±5S

ELECTRICAL

VOLTAGE RATING

: 125 VAC RMS

CURRENT RATING

: 1.5 AMP

CONTACT RESISTANCE

: 20 mΩ MAX.

INSULATION RESISTANCE

: 1000 MΩ MIN. @500V DC

DIELECTRIC STRENGTH

: 1000V DC OR AC PEAK CONTACT  
TO CONTACT OR 1500V DC OR AC  
CONTACT TO SCREEN AND TEST  
PANEL @0.5mA 50Hz OR 60Hz  
ONE MINUTE

ENVIRONMENTAL

STORAGE

: -40°C ~ +85°C

OPERATION

: -40°C ~ +85°C

		UNIT	mm
		REVISION	03
PRODUCT		TOLERANCES	
RJ45 1X2 SIDE ENTRY JACK WITH LED		00~15 ± 0.15 15~30 ± 0.20 30~ ± 0.25	
DWG NO.	PART NO.	ANGLES ± 1°	
EZC1145-28S21-01			
PROJECTION	SCALE	SHEET	1 OF 1