



- NOTES:
- MECHANICAL**
 - HOUSING : LCP UL94V-0 BLACK
 - CONTACT : PHOSPHOR BRONZE
 - PLATING : CONTACT AREA SELECTIVE GOLD PLATING SOLDER AREA TIN PLATING NICKEL PLATING OVERALL
 - DURABILITY : 750 CYCLES MIN.
 - MATING/UNMATING FORCE : 30N MAX.
 - RETENTION STRENGTH : 50N MIN.
 - ELECTRICAL**
 - VOLTAGE RATING : 150VAC RMS
 - CURRENT RATING : 1.5 AMPS
 - CONTACT RESISTANCE : 20 mΩ MAX.
 - INSULATION RESISTANCE : 1000 MΩ MIN. @500V DC
 - DIELECTRIC STRENGTH : 1500V DC OR 1000V AC RMS @0.5mA 50Hz / 60Hz ONE MINUTE
 - ENVIRONMENTAL**
 - STORAGE : -40°C ~ +85°C
 - OPERATION : -40°C ~ +85°C

		UNIT	mm
		REVISION	25
PRODUCT		RJ11 1X1 TOP ENTRY JACK SMT	
DWG NO.		PART NO.	
EZC745-14N11-01			
PROJECTION	SCALE	SHEET	1 OF 1

TOLERANCES

0 ± 0.30
 00 ± 0.20
 000 ± 0.10
 ANGLES ± 0.5°